

REPORT DOCUMENTATION PAGE

AFRL-SR-AR-TR-03-

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188).

1. AGENCY USE ONLY (Leave blank)**2. REPORT DATE****3. REPORT TYPE**

0437

01 May 2000 - 30 Apr 2003 Final Report

4. TITLE AND SUBTITLECOATING CONDUCTORS WITH THE HIGHEST-TC HG-BASED
SUPERCONDUCTORS**5. FUNDING NUMBERS**

61102F

2305/GX

6. AUTHOR(S)

Dr Wu

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)University of Kansas
Center for Research Inc
2385 Irving Hill Road
Lawrence KS 66044-7552**8. PERFORMING ORGANIZATION
REPORT NUMBER****9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)**AFOSR/NE
4015 WILSON BLVD
SUITE 713
ARLINGTON VA 22203**10. SPONSORING/MONITORING
AGENCY REPORT NUMBER**

F49620-00-1-0303

11. SUPPLEMENTARY NOTES**12a. DISTRIBUTION AVAILABILITY STATEMENT**

APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED

12b. DISTRIBUTION CODE**13. ABSTRACT (Maximum 200 words)**

This project started on April 1, 2000 and was completed on April 30, 2003. The overall goal of the project is to develop novel processes, such as the cation exchange process, for epitaxy of 1-Ig-based high temperature superconducting (Hg-HIS, mainly Trig-1212 of $T_c \sim 125$ K and Hg-1223 of $T_c \sim 135$ K) thin films on metal substrates. Four students were partially supported during the reporting period. Research on the two research objectives has been carried out in parallel and exciting progress has been made, as summarized in the following. Details of our results may be found in 1 book chapter, 28 papers (24 published/accepted, and 4 submitted), 1 US patent awarded and 2 patent disclosures submitted. In addition, two Ph.D. students graduated during the project period. Dr. Yiyuan Xie graduated in March of 2002 and joined IGC immediately afterwards and Dr. Roberto Aga, in December 2002 with honor, and now stay as a postdoctoral research at the University of Kansas.

20031028 122

14. SUBJECT TERMS**15. NUMBER OF PAGES****16. PRICE CODE****17. SECURITY CLASSIFICATION
OF REPORT**

UNCLASSIFIED

**18. SECURITY CLASSIFICATION
OF THIS PAGE**

UNCLASSIFIED

**19. SECURITY CLASSIFICATION
OF ABSTRACT**

UNCLASSIFIED

20. LIMITATION OF ABSTRACT

UL

Standard Form 298 (Rev. 2-89) (EG)
Prescribed by ANSI Std. Z39.18
Designed using Perform Pro, WHS/DIOR, Oct 94

Coating Conductors with the Highest- T_c Hg-based Superconductors

AFOSR Grant/Contract #F49620-00-1-0303

KUCR #: 22920

Final Report

April 1, 2000— April 30, 2003

PI Name: Judy Wu

PI Address: Dept. of Phys., Univ. of Kansas, Lawrence, KS 66045

PI phone: (785)864-3240

PI fax: (785)864-5262

PI email: JWU@KU.EDU

Summary

This project started on April 1, 2000 and was completed on April 30, 2003. The overall goal of the project is to develop novel processes, such as the cation exchange process, for epitaxy of Hg-based high temperature superconducting (Hg-HTS, mainly Hg-1212 of $T_c \sim 125$ K and Hg-1223 of $T_c \sim 135$ K) thin films on metal substrates. Four students were partially supported during the reporting period. Research on the two research objectives has been carried out in parallel and exciting progress has been made, as summarized in the following. Details of our results may be found in 1 book chapter, 28 papers (24 published/accepted, and 4 submitted), 1 US patent awarded and 2 patent disclosures submitted. In addition, two Ph.D. students graduated during the project period. Dr. Yiyuan Xie graduated in March of 2002 and joined IGC immediately afterwards and Dr. Roberto Aga, in December 2002 with honor, and now stay as a postdoctoral research at the University of Kansas.

Major experimental results

Under the AFOSR supports, the KU group has actively worked on coated conductors during the past few years. One major progress is in development of novel processes for epitaxy of the Hg-HTS films and coated conductors (three US patents awarded and one pending). Hg-HTSs have T_c s up to 135 K, the highest among HTSs, and intrinsically high irreversible fields with $H_{irr}(77K) \sim 4-5$ T and $H_{irr}(100K) \sim 1$ T. The higher T_c s allow higher operation temperatures, which implies significantly reduced cryogenic requirements and operation costs. In fact, the cooling requirement may be eliminated for many space-related applications as the background temperature in deep space is ~ 80 K. On Hg-HTS thin films grown on single-crystal LaAlO_3 substrates, we have achieved J_c values near 2 MA/cm^2 at 100K and self field, which are about two orders of magnitude higher than those of any existing superconductors. These films have superior microwave properties and prototype microwave devices are under development in collaboration with the Superconductor Technology, Inc. Through collaboration with ORNL, a $J_c(100K) \sim 1 \text{ MA/cm}^2$ has also been demonstrated on Hg-1212 coated $\text{CeO}_2/\text{YSZ}/\text{CeO}_2/\text{RABiTs}$ tapes. This makes Hg-HTS coated conductors very appealing for power-related applications at 100 K or higher.

Our AFOSR project had two major focuses: developing processes to scale up Hg-1212 coated conductors, and exploring ways to improving the magnetic pinning strength of them. For the former, we have developed a batch processing technique and demonstrated that uniform Hg-1212 coated conductors over 10 cm Buffered Ni substrates. This technique can be applied for longer tapes when substrates are available. In collaboration with ORNL and LANL, we have shown that the magnetic flux pinning properties can be significantly improved on Hg-HTS films when linear defects are introduced either using GeV ion beam irradiation or substrate engineering. The latter is extremely appealing since it can be scaled up for long length processing. The H_{irr} of Hg-1212 and Hg-1223 has been increased to about 6T at 77 K and ~3 T at 100 K, adequate for many power-related applications at temperatures near and above 77 K.

Objective 1: Research on fundamental issues related to and development of schemes for scale-up of Hg-HTS coated conductors

- **Large area**—Many applications require large-area thin films. Synthesis of Hg-HTS materials requires a high vapor pressure of Hg in the range of 5-10 atm. To generate and maintain such pressures, the precursor samples of desired nominal composition have to be torch sealed with the Hg-vapor source (e.g. HgO, HgF₂, HgCl₂, HgCaO₂, etc) in evacuated quartz ampoules for heat treatments to form Hg-HTS materials. We recently developed a reusable crucible technique that allows epitaxy of Hg-HTS films in a dynamic equilibrium of Hg and oxygen vapors, instead of a static equilibrium as in the sealed quartz ampoule. In addition, the crucible can be reused repeatedly and has no size restriction. In a preliminary test, we have obtained samples of quality comparable to that from in the sealed quartz ampoule technique. This technique is a very important step in scale up the Hg-HTS films to large area for various applications in both electronics and electrics. Our future effort will be in optimizing each step and finalizing the design of the crucible.
- **Long length**—HTScc must have long length for applications. We recently developed a batch process for scaling up Hg-HTS coated conductors (Hg-HTScc). The precursor tapes are wound around a source cylinder that is to provide either Tl or Hg vapor when heated in a commercial tube furnace. We have demonstrated that uniform physical properties (XRD, T_c and J_c) can be obtained on Tl-HTS and Hg-HTC coated conductors of several cm long. For example, the end-to-end J_c (77 K) in exceeding 1 MA/cm² has been obtained on 2-cm long Hg-1212/Ni tapes. Experiments on longer tapes are underway in collaboration with doe labs and our focus will be to optimize the process for long tape fabrication.

Objective 2: Study of vortex dynamics and optimization of pinning strength in Hg-HTS coated conductors

One of the Air Force specifications for HTS coated conductor applications is the high irreversibility field H_{irr} in the range of 2-5 T at 77K. Hg-HTS has its original H_{irr} ~ 2-3 T at 77 K so improvement of H_{irr} is necessary. Last year, we demonstrated that the H_{irr} of Hg-1212 film is significantly improved with introduction of linear defects along the c-axis using GeV ion beam irradiation. For example, the H_{irr} was increased to ~ 6T at 77K and ~ 3T at 100K. This year's focus

has been on exploring practical ways to improve the H_{irr} and two schemes turned out to be successful: oxygen overdoping and substrate engineering. Details will be given in the following.

- **Oxygen Overdoping**—HTS's properties are sensitively determined by the oxygen content and the best J_c and H_{irr} are obtained when samples are moderately overdoped. For Hg-HTS, we developed a simple Fluorine-assisted process that allows oxygen overdoping in Hg-HTS at atmospheric pressures. The J_c s of overdoped Hg-1212 films were increased fairly uniformly over a wide temperature range by a factor of 2 and the H_{irr} significantly. For example, at 77 K, H_{irr} is increased by more than 50%, and this improvement is more significant at lower temperatures. The future research will be on understanding the mechanism of this Fluorine-assisted process. In addition, overdoping grain-boundaries will also be investigated using this technique.
- **Substrate Engineering**—HTS films show different microstructures when grown on different substrates. Linear growth defects could be formed when there is additional strain generated in film when substrate has a small vicinal angle with respect to the normal of the substrate. These linear defects may mimic the role of those generated by GeV ion beam irradiation, resulting in improved H_{irr} . On 4° STO vicinal substrates, we demonstrated recently that both in-field J_c and H_{irr} are improved. For example, at 77 K and $H = 2T$, J_c is one order of magnitude higher in Hg-1212 film on 4° STO vicinal substrate than the same film on flat STO substrates. The H_{irr} at 77 K is enhanced by more than 30% on the former. The ongoing research is study the effect of vicinal angle on the J_c s and H_{irr} so as to optimize the improvement. In addition, we are exploring ways to generate vicinal buffers so that improved J_c s and H_{irr} can be obtained on coated conductors.

In addition to research on growth of coated conductors, we have also worked on development of appropriate tools for coated conductors characterization (partially from our AFOSR/MURI support). Scanning probe microscopy (SPM) has been a useful tool [20] for this purpose but most commercial SPM measures one physical property at a time. This is in sharp contrast to the need to correlate different physical property at a nanometer scale in most practical research and applications. Motivated by such needs to correlate different physical properties at a microscopic scale, we have recently developed a dual-channel scanning probe microscope (a US patent pending). The novel feature of this invention is that it uses a coaxial multi-layered probe design, with each layer (made using high-vacuum thin film coating process) serves as a channel for different input/output signal. Since the layer thickness is in the nanometer regime, this multi-layered probe allows imaging/mapping of two or more different properties at the same pixel simultaneously. For example, an optical fiber tapered to few tens of nanometers in diameter can be used for transferring optical signals. Coating this fiber with a thin layer of metals (Al, Au, etc) will make the fiber electrically conducting. If this fiber is used as the center conductor of a $\frac{1}{4}$ wavelength coaxial resonator, both optical and microwave signals can be transferred through the probe. This near-field scanning optical/microwave dual-probe microscope (NSOM/NSMM) has been demonstrated experimentally in PI's lab recently [21] and will provide a unique tool for mapping physical properties of the coated conductors

Publications

Patents:

1. (Patent Disclosed) R. Aga and J.Z. Wu, "Development of Near-field Scanning Optical/microwave Dual Probes", submitted Nov. 15, 2001.
2. (Patent Disclosed) Y.Y. Xie and J.Z. Wu, "Re-usable crucible technique for large area epitaxy of Hg-based high-temperature superconducting wafers and long-length tapes", submitted Oct. 18, 2001.
3. U.S. patent 6395685 (2002), J.Z. Wu, S.L. Yan, and Y.Y. Xie, "Thin Film Hg-Based Superconductors and Method of Fabrication Thereof".

Ph.D. Thesis:

21. R. Aga, Jr., honorable thesis, "Development of Dual-channel Scanning Optical/microwave microprobe microscopy", Department of Physics and Astronomy, University of Kansas, December 2002.
22. Y.Y. Xie, "Epitaxy of Hg-based high temperature superconducting films on oxide and metal substrates", Department of Physics and Astronomy, University of Kansas, May 2002.

Books and articles:

1. (Book chapter) J.Z. Wu, "Epitaxy of Hg-based high temperature superconducting thin films", book chapter in *Next generation High Temperature Superconducting Wires*, edited by A. Goyal, Plenum Publishing
2. Y.Y. Xie, J.Z. Wu, S.H. Yun, R. Emergo, and R. Aga, "Magnetic flux pinning enhancement in vicinal $\text{HgBa}_2\text{CaCu}_2\text{O}_{6+\delta}$ films", submitted to Appl. Phys. Lett.
3. R. Aga and J.Z. Wu, "Near-field Scanning Optical/microwave Dual Probe", submitted to Appl. Phys. Lett.
4. Z.W. Xing and J.Z. Wu, "Reversible cation exchange in "1212" superconductors", submitted to Appl. Phys. Lett.
5. Z.W. Xing, Y.Y. Xie and J.Z. Wu, "Fabrication of 3 μm thick Hg-1212 films in cation exchange process", submitted to Physica C.
6. Y.Y. Xie and J.Z. Wu, "Significantly enhanced critical current density in overdoped Hg-1212 thin films", Appl. Phys. Lett. **82**, 2856 (2003).
7. S.L. Yan, J.Z. Wu, L. Fang, Y.Y. Xie, T. Aytug, A.A. Gapud, and B.W. Kang, "Microstructural evolution in converting epitaxial Tl-2212 thin films to Hg-1212 Thin films using cation-exchange process", J. Appl. Phys. **93**, 1666 (2003).
8. Yiyuan Xie, Albert Gapud, Judy Z. Wu, Yang Yu, and Siyuan Han, "HgBa₂CaCu₂O_x superconducting microbridges using cation-exchange process: a new approach in thin film device fabrication", submitted to Supercon. Sci. &Tech.
9. Y.Y. Xie and J.Z. Wu, T. Aytug, D.K. Christen, A. Cardona, "Cation and anion diffusion kinetics in Hg-1212 films made in Cation exchange process", Appl. Phys. Lett. **81**, 4002 (2002).
10. R.S. Jr. Aga, Y.Y. Xie, and J.Z. Wu, "Surface characterization of Hg-1212 films by atomic force microscopy", Proceeding of National Academy of Science, special issue, Nanoscience and the Underlying Physics.
11. R.S.Jr. Aga, S.L. Yan, Y.Y. Xie, and J.Z. Wu, "Passivation Effects of Polymethyl Metacrylate on Superconducting HgBa₂CaCu₂O_{x+\delta} thin films", Physica C **366**, 216 (2002).
12. J.Z. Wu, Y.Y. Xie, Z.W. Xing and R.S. Aga, "Recent progress in epitaxy of Hg-HTS thin films on oxides and metals", Physica C **382**, 62 (2002).

13. R N. Bhattacharya, Z. Xing, J. Z. Wu, J. Chen, S. X. Yang, Z. F. Ren, and R. D. Blaugher, "Superconducting Thallium Oxide and Mercury Oxide Films", *Physica C* **377**, 327 (2002).
14. C. Kim, A. Metha, D.L. Feng, K.M. Shen, N.P. Armitage, K. Char, S. Moon, Y. Xie and J. Wu, "X-ray diffraction measurements of the c-axis Debye-Waller factors of YBCO and Hg-1212", *Phys. Rev. B* **67**, 092508 (2003).
15. R.S.Jr. Aga, S.L. Yan, Y.Y. Xie, and J.Z. Wu, "Passivation Effects of Polymethyl Metacrylate on Superconducting $\text{HgBa}_2\text{CaCu}_2\text{O}_{x+\delta}$ thin films", *Physica C* **366**, 216 (2002).
16. R. Aga Jr., Yi-Yuan Xie and Judy Z. Wu, "Real-time Degradation Study of $\text{HgBa}_2\text{CaCu}_2\text{O}_{6+\delta}$ Thin Film Using a Combined Microwave and Optical Near-field Scanning Probe", MRS proceeding, Boston, Nov.25-30, Vol. 689, 93(2001).
17. Y. Xie, J.Z. Wu, T. Aytug, D.K. Christen, A.H. Cardona, "Diffusion mechanism of cation-exchange process for fabrication of $\text{HgBa}_2\text{CaCu}_2\text{O}_{6+\delta}$ superconducting films", MRS proceeding, Boston, Nov.25-30, Vol. 689, 107(2001).
18. R N. Bhattacharya, Z. Xing, J. Z. Wu, J. Chen, S. X. Yang, Z. F. Ren, and R. D. Blaugher, "Superconducting Thallium Oxide and Mercury Oxide Films", MRS proceeding, Boston, Nov.25-30, Vol. 689, 1113(2001).
19. A. Gapud, J.Z. Wu, B.W. Kang, "Normal-state Hall effect in '1212' superconductors", *Phy. Rev. B* **64**, 052502 (2001).
20. T. Aytug, B.W. Kang, C. Catoni, E.D. Specht, M. Paranthaman, A. Goyal, D.K. Christen, D.T. Verebelyi, J.Z. Wu, R.E. Ericson, C.L. Thomas, C.Y. Yang and S.E. Babcock, "Growth and Characterization of conductive SrRuO_3 and LaNiO_3 multilayers on textured Ni tapes for high- J_c YBCO coated conductors", *J. of Mat. Res.* **16**, 2661 (2001).
21. T. Aytug, Y.Y. Xie, J.Z. Wu, D. K. Christen, "Growth characteristics of $\text{HgBa}_2\text{CaCu}_2\text{O}_6$ superconducting films on CeO_2 -buffered YSZ single crystals: an assessment for coated conductors", *Physica C* **363**, 107 (2001).
22. R.S. Aga, Y.Y. Xie, S.L. Yan, J.Z. Wu and S. Han, "Microwave Power Handling Capability of $\text{HgBa}_2\text{CaCu}_2\text{O}_{6+\delta}$ Thin Films", *Appl. Phys. Lett* **79**, 2417 (2001).
23. J.Z. Wu, "Cation exchange, synthesis and epitaxy of Hg-HTSs via atomic perturbation", invited paper in Proceeding of SPIE Aerosense Conference, Orlando, Florida, 24-28 April 2000.
24. W. N. Kang, Wan-Seon Kim, Sung-Ik Lee, B. W. Kang, J. Z. Wu, Q. Y. Chen, W. K. Chu, and C. W. Chu, "Mixed-state Hall effect in Hg- and Tl-based superconducting thin films", *Physica C*, **341-348**, 1235 (2000).
25. T. Aytug, J.Z. Wu, B.W. Kang, D.T. Verebelyi, C. Cantoni, E.D. Specht, A. Goyal, M. Paranthaman, and D. K. Christen, "An all-sputter buffer layer architecture for high- J_c YBCO coated conductors", *Physica C* **340**, 33 (2000).
26. Y.Y. Xie, T. Aytug, J.Z. Wu, D.T. Verebelyi, M. Paranthaman, A. Goyal, and D. K. Christen, "Epitaxy of Hg-1212 superconducting films on biaxially textured Ni substrates", *Appl. Phys. Lett.* **77**, 4193 (2000).
27. L. Fang, S.L. Yan, A.A. Gapud, T. Aytug, B.W. Kang, Y.Y. Xie, J.Z. Wu, S.C. Tidrow, M.H. Ervins, and K.W. Kirchner, "High-Temperature Superconductivity in very-thin Hg-1212 films", *Physica C* **339**, 253 (2000).
28. R.S. Aga, Y.Y. Xie, J.Z. Wu and S. Han, "Microwave Characterization of $\text{HgBa}_2\text{CaCu}_2\text{O}_{6+\delta}$ Thin Films", *Physica C* **341-348**, 2721 (2000).
29. Yi-Yuan Xie, Tolga Aytug, Judy Z. Wu, and D. K. Christen, "Growth and Physical Properties of Hg-1212 HTSC Tapes on Buffered Metal substrates", *Physica C* **341-348**, 2505 (2000).